





Photovoltaic storage inverters

model	M4835P
Power	3.5KW

Functional Description

- Distinguish traditional buttons, using high-definition touch capacitive screen.
- Industrial UI design, interface display is more intuitive, more convenient operation.
- Support management upgrading and customization of user's special needs.



- New management software system, more intuitive display, more convenient operation .
- Industrial UI design, friendly interactive interface, higher readability.
- Comprehensive real-time data monitoring and collection.
- Advanced MPPT technology, optical storage and charging in one.
- Efficient power generation and power management control platform
- The system automatically utilizes peaks and valleys to regulate charging and discharging to save electricity costs.
- Maximum support current of 25A and voltage of 450V for single circuit PV.
- Perfectly adapted to high-power photovoltaic modules
- Working environment monitoring at the right time, multiple protection
- High-quality sine wave output with SPWM regulation technology.
- Automatic air-cooling adjustment, more stable operation, and the operation status can be seen at a glance.
- Supports User-defined policies, logical event-driven.
- Unique lithium BatteryBMS management technology
- Support lithium BatteryBMS bi-directional communication
- Multiple Battery Types, Maximum Charging Current 100A
- Support management upgrade, compatible with more BMS



Model	M4835P	settable
inverter output		
Rated output power	3.5KW	
Max. peak power	7KW	
Rated output voltage	L+N+PE 208/220/230/240Vac	Y
Carrying motor capacity	2HP	
rated power	50/60HZ	
Output Waveform	pure sine wave	
switching time	10ms(typical value)	
Number of parallel machines	not support	
Battery		
Battery type	lead-acid battery/lithium ion battery/User-defined	Y
Rated Battery Voltage	24V	
Voltage range	20-30Vdc	Y
Maximum photovoltaic charging current	80A	Y
Maximum mains/generator charging current	80A	Y
Maximum hybrid charging current	80A	Y
Photovoltaic input		
Number of MPPT paths	1	
Maximum Input Power	5000W	
Maximum Input Current	18A	
Maximum Open Circuit Voltage	500Vdc	
MPPT working Voltage range	40-450Vdc	
Mains/generator input		
Input Voltage range	UPS: 170-264Vac; APL: 90-280Vac	Y
Input frequency range	50/60HZ	
Bypass overload current	20A	
Efficiency Efficiency		
MPPT Tracking Efficiency	99.5%	
Battery inverter efficiency	93.5%	
Basic parameters		
Size	430*314*118mm	
Weight	9kg	
Protection level	IP21	
environmental temperature	-20-55°C, > 40°C degraded to 80%,	
Humidity range	20%-95% non-condensing	
Cooling method	Built-in fan	
Warranty Time	2 years	
communication		
built-in interface	RS485/CAN/USB/dry contact	